



ExploreX

SCISSOR LIFT PONTOON TRAILERS

The Scissor Lift Pontoon Trailer will allow you to launch your Pontoon no matter what obstacles the boat access gives you even in shallow water.



**Standard Models:
PSL1820, PSL2123, PSL2426**

The Trailer will also allow you to drop your pontoon to the ground.



**Economy Models:
PSL20E, PSL24E**


DM

**DONNER
MANUFACTURING**

CLARA CITY, MN | 320-847-2200

WWW.DONNER-MFG.COM


SCISSOR LIFT PONTON TRAILER SPECIFICATIONS



**Heavy Duty Winch
Stand With Brake &
Double Pulley System**



**Sturdy Cross Brace
With Nylon Bushings
(Standard Models Only)**



**Adjustable Side
Centering Rollers
(Standard Models Only)**



**Tie Downs Front
And Back**

MODEL	PSL20E	PSL24E	PSL1820	PSL2123	PSL2426	
Boat Length	To 20'	To 24'	To 20'	To 23'	To 26'	
Standard Carrying Capacity	2230 lbs	2110 lbs	2110 lbs	2070 lbs	1910 lbs	
Carrying Capacity W/Brakes	2920 lbs	3300 lbs	3300 lbs	3260 lbs	3100lbs	
Tire Size	5.30x12C	5.30x12C	5.30x12C	5.30x12C	5.30x12C	
Overall Width	43"	43"	43"	43"	43"	
Frame Size	2"x 3"	2"x 4"	2"x 3"	2"x 4"	2"x 4"	
Loading Height	20"	20"	22"	22"	22"	
Hauling Height	38"	38"	40"	40"	40"	
Axles (Torsion)	2	2	2	2	2	
Tongue Jack	STD.	STD.	STD.	STD.	STD.	
Lights	STD.	STD.	Submersible LED			
Paint	Coated Gloss Black					
Adjustable Side Guide Rollers	None	None	Standard			
Approximate Ship Weight	760	880	880	920	1080	

Hitch height based on standard tires, upgraded tires will change hauling heights. Pricing and specifications may change without notice. **Important:** It is the responsibility of the purchaser to comply with the brake laws regarding trailers. For full information regarding the laws in your state, contact the appropriate State Motor Vehicle Department. Brake options will change the overall length of trailer. Brake option is surge brakes on all pontoon trailers. Recommended tongue weight 7-10% of GVWR.